

ME Civil Engineering First Year Second Semester Examination 2025

Air Pollution and Control

Time: Three Hours

Full Marks: 100

Part 1

(60 marks for Part 1 & 40 marks for Part 2)

Answer Question No. 1 and any Two from the rest. Turner's σ_y & σ_z curves and Pasquill's stability chart related with Gaussian Air Pollution Model (GAPM) may be used. Any relevant data may be assumed, if necessary.

1.
 - i) What is a Gaussian Air Pollution Model (GAPM)?
 - ii) What is the significance of 'flat terrain' assumption in GAPM?
 - iii) Why is molecular diffusion neglected in GAPM?
 - iv) With a sketch define 'SW' wind.
 - v) With a sketch show how 'downwind' direction in GAPM is selected.
 - vi) With a sketch show the origin of the coordinate system of GAPM located.
 - vii) In which modified forms of GAPM σ_z is missing (give a sketch)?
 - viii) With a sketch show the roll of 'image source' in GAPM.
 - ix) Why is centerline modifications of GAPM important?
 - x) What is the full form and significance (with respect to GAPM) of 'insolation'?
 - xi) Holland's Plume Rise Model was developed imperially perhaps during neutral condition' – explain.
 - xii) Comment about correction of 'p' used in wind profile power law.
 - xiii) Define 'night' as per Pasquill Stability Class Chart.
 - xiv) What are the vertical constraints with respect to GAPMs?
 - (xv) Define a plume.

2 x 15 = 30

[Turn over

ME Civil Engineering First Year Second Semester Examination 2025**Air Pollution and Control****Part 1 (60 marks for Part 1 & 40 marks for Part 2)**

2. a) The general Gaussian expression is as follows:
- $$C_{(x,y,z;H)} = Q/(2\pi \sigma_y \sigma_z U) [\text{Exp}\{-y^2/2 \sigma_y^2\}] [\text{Exp}\{-(H-Z)^2/2 \sigma_z^2\} + \text{Exp}\{-(H+Z)^2/2 \sigma_z^2\}]$$
- The notations have their usual meanings.
- The second exponential term in the vertical factor is due to one modification. With a sketch explain that modification.
- Now find expressions for following modifications
- (i) receptors on ground level (ii) maximum concentration
- b) A stack emitting 100 g/sec of NO has an effective stack height of 100m. The wind speed at stack tip is 4.5m/s and it is an overcast day. Estimate the ground level NO concentration at:
- (i) directly downwind at a distance 500m (ii) at a point (500,200,0), Comment on the result. 8+7= 15
3. a) A burning solid waste dump emits 20 g/s of oxides of nitrogen (NO_x). What may be the concentration of NO_x directly downwind from the source at a distance of 3 km on an overcast night with wind speed 6m/s? The background concentration of NO_x at the receptor location is 50µg/m³.
- b) A stack with effective height 45m, emitting at the rate of 150 g/s. Winds are estimated at 5 m/s at the stack height, the stability class C, and there is an inversion at 100 m. Estimate the ground-level concentration at the point where reflections begin to occur from the inversion and at a point twice the distance downwind. What may be the type of inversion? What may be the probable plume pattern?
- c) What are the significance of following coordinates with respect to Gaussian Coordinate System?
- (i) (0, 0, -H) (ii) (x, 0, H) (iii) (x, 0, 0) (iv) (0, 0, h) and (v) (0, 0, 0) 4+6+5=15

ME Civil Engineering First Year Second Semester Examination 2025**Air Pollution and Control**

(60 marks for Part 1 & 40 marks for Part 2)

Part 1

Time: Three Hours

Full Marks: 100

4. a) What is a line source model? Why is σ_y missing in the expression of a line source model?
 b) What is a source appointment study? Why is it very relevant for controlling NO?
 c) Explain the role of GAPM in an EIA study.
 d) If you are given some fund for betterment of air quality of your locality, how will you spend the fund?
 e) What may be the roll of air quality models in management of area sources? 3x5 =15

Some of the following equations may be required (notations have their usual meanings):

- | | | |
|---|---|--|
| 1) $\Delta h = 2.6 (F/uS)^{1/3}$ | 2) $F = gr^2 v_s (1 - T_a/T_s)$ | 3) $S = (g/T_a)(\Delta T_a/\Delta z + 0.01^\circ\text{C/m})$ |
| 4) $\Delta h = [1.6F^{1/3}(x_f)^{2/3}]/u$ | 5) $x_f = 120 F^{0.4}$, if $F \geq 55\text{m}^4/\text{s}^3$ | 6) $x_f = 50 (F)^{5/8}$ if $F \leq 55\text{m}^4/\text{s}^3$ |
| 7) $C = Q / [(2\pi)^{1/2} u \sigma_y L]$ | 8) $\Delta h = [v_s d / u] [1.5 + 2.68 \times 10^{-3} p (1 - T_a/T_s) d]$ | |
| 9) $C_{(x,y,0:H)} = [2q/(2\pi)^{1/2} \sigma_z u \sin\theta] [\text{Exp}(-H^2/2 \sigma_z^2)]$ | | |

[Turn over

M.E. CIVIL ENGINEERING 1st YEAR 2nd SEMESTER EXAMINATION, 2025

SUBJECT: Air Pollution and Control (EE)

Full Marks 100
(40 marks for part II)

Time: Three hours

Use a separate Answer-Script for each part

Part-II

Answer all question

*(Assume any data, if required, reasonably)**(Lapple's Efficiency Curve may be used)*

1.
 - a) What are the different types of NO_x and SO_x generation from furnace? Describe one post-combustion regenerable wet system of flue gas desulfurisation. 10
 - b) What is the significance of isokinetic sampling in stack monitoring? In a 2 m diameter stack, it is decided that number of sampling points will be 12. Find out the location of the sampling points. 10
2.

An air stream with a flow rate of 7 m³/s is passed through a cyclone of standard properties. The diameter of the cyclone is 1.8 m. and the viscosity of air is 2.1×10⁻⁵ kg/m.s. Determine the amount of removal/m³ of flue gas, for particles with a density of 1.65 g/cm³ and diameter of 6µm and 11µm (40:60 w/w) when their total concentration is 370 µg/m³ of flue gas. 10
3.
 - a) Design a parallel plate single-stage electro static precipitator (ESP) from the following data:
Required efficiency = 99.5%; Gas flow rate = 2,00,000 m³/hr
Particle drift velocity = 0.15 m/s; Collectrode spacing = 0.3 m %
Depth of collectrode = 3m; Height of collectrode = 6m; Gas flow velocity = 1.78 m/s 10